## WORLD INTELLECTUAL PROPERTY ORGANIZATION



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

**A1** 

(11) International Publication Number:

WO 99/30656

A61F 9/013

(43) International Publication Date:

24 June 1999 (24.06.99)

(21) International Application Number:

PCT/US98/26966

(22) International Filing Date:

16 December 1998 (16.12.98)

(30) Priority Data:

08/993,445

18 December 1997 (18.12.97)

(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application

US

08/993,445 (CIP)

Filed on

18 December 1997 (18.12.97)

(71) Applicant (for all designated States except US): KERAVI-SION, INC. [US/US]; 48630 Milmont Drive, Fremont, CA 94538-7353 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): GANDIANCO, Isidro [US/US]; 36520 Alder Court, Fremont, CA 94536 (US). SCHOLL, John, A. [US/US]; 14 Woodranch Circle, Danville, CA 94506 (US).

(74) Agents: BECKING, Frank, P. et al.; Morrison & Foerster LLP, 755 Page Mill Road, Palo Alto, CA 94304-1018 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR. KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: CORNEÁL POCKETING TOOL

(57) Abstract

The invention relates to a corneal pocketing tool for separating the lamella of the comea. The comeal pocketing tool has a dissector portion for insertion into a comeal incision and a reference surface or region adapted to contact the comea. As the dissector is advanced into the comeal incision the reference region comes into contact with the surface of the comea and resists further advancement of the dissector. As the reference region is moved in a clockwise or counterclockwise direction, the dissector portion follows in the same direction forming a pocket in the cornea.



## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania .	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	. LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegai
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	· MC	Monaco	TD ·	Chad .
BA	Bosnia and Herzegovina	·GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ ·	Tajikistan
BE	Belgium	GN	Guinea .	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece .		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	. Mali	TT	Trinidad and Tobago
BJ	Benin	1E	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada .	IT	Italy	MX	Mexico	UZ	Uzbekistan .
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL.	Netherlands	ΥU	Yugoslavia
СН	Switzerland	KĠ	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	· NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL.	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania	•	
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan .		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

#### CORNEAL POCKETING TOOL

#### FIELD OF THE INVENTION

This invention involves a surgical instrument for intracorneal pocketing. The handheld surgical tool is typically inserted into a corneal incision and maneuvered to create a corneal pocket. This invention also provides a method for creating an intracorneal pocket.

## BACKGROUND OF THE INVENTION

10

5

Anomalies of the overall shape of the eye often cause appreciable visual disorders, such as hyperopia, myopia, and astigmatism. The surgical treatment of these and other disorders often involve creating a separation or pocket between the stromal layers of the cornea. Various materials, substances, or inserts may be placed within the pocket to effectuate changes in the geometry of the cornea or deliver drugs or other biologic agents.

15

20

For example, these disorders may be corrected using surgical methods involving the implantation of polymeric rings (intrastromal corneal rings) in the eye's corneal stroma to change the curvature of the cornea. Previous work involving the implantation of polymethylmethacrylate rings, allograft corneal tissue, and hydrogels is well documented. One of the ring devices involves a split ring design which is inserted into a pocket in the form of an annular channel dissected in the stromal layer of the cornea. See, for instance, the use of intrastromal rings in U.S. Patents Nos. 4,452,235 to Reynolds; 4,671,276 to Reynolds; 4,766,895 to Reynolds; and 4,961,744 to Kilmer et al. Temirov et al., "Refractive circular tunnel keroplasty in the correction of high myopia", Vestnik Oftalmologii 1991: 3-21-31, suggests the use of collagen thread as intrastromal corneal ring material.

25

It is also known to use arcuate channels containing a gel-based insert centered on the cornea to correct certain visual disorders. U.S. Patent Nos. 5,090,955 and 5,372,580, to Simon, suggest introducing a settable polymer or gel into an intrastromal channel and allowing the polymer to set.

30

These types of procedures typically involve making a partial depth incision into the cornea, either radial or circumferential, and then separating the lamella at a known depth.

The separation may be continued or furthered, using a variety of instruments as necessary, until the desired channel or pocket is formed at the desired depth below the surface of the cornea. In U.S. Patent No. 5,547,468 to Simon et al., for example, once the incision has been formed, a blunt spatula is inserted through the incision to separate the lamella. Following this initial separation of lamella with the blunt spatula, a channel starting instrument is inserted into the incision and then rotated in a manner such that the lamella is separated along an arcuate path.

Creation of the initial separation using an ordinary blunt spatula is often very difficult. There is little visual access to the tip of the instrument at the base of the incision and it may be difficult for the surgeon to feel the bottom of the incision. Improper placement or inadequate manipulation of the instrument by the surgeon may result in an initial separation at the wrong depth relative to the surface of the cornea or no separation at all. Excessive manipulation of the spatula in attempting to initiate the separation at the base of the incision may result in damage or trauma to the incised tissue as well as the tissue below the incision.

There is a need therefor for a pocketing tool constructed to provide a reliable lamella separation at the desired depth below the surface of the cornea which is less sensitive to manipulation difficulties inherent in prior art instruments.

### SUMMARY OF THE INVENTION

20

15

5

10

This invention is a surgical instrument for separating the lamella of a cornea. The instrument has a dissector and a reference region adapted to contact the surface of the cornea. In one aspect of the present invention, the dissector is disposed at an angle relative to said reference region of between about 30° and about 150°, preferably less than about 110°.

25

30

The reference region may comprise a planar surface or a curved surface. If the reference region is configured to have a curved surface, it will typically have a radius of curvature in the range of about 6 mm to about 10 mm.

As the dissector is inserted into the incision, the free advancement of the dissector is prevented once the reference surface comes into contact against the surface of the cornea.

5

10

15

20

25

The reference region and the dissector, being disposed in an angular relation to one another, converge at an intersection. The instrument handle may then be manipulated to cause the dissector to rotate about a point near the intersection. The intersection of the reference region and the dissector may take the form of a radius or radiused surface. The radius in conjunction with the reference region provide a suitable pivot about which the dissector may be rotated to initiate the desired separation at the dissector tip.

The present invention also involves a method of creating an intrastromal separation or pocket at the base of a partial-depth corneal incision involving inserting an instrument having a reference surface in angular relation to a dissector until the reference surface contacts the surface of the cornea and rotating the instrument about the vertex of the intersection of the reference region and the dissector.

The above is a brief description of some deficiencies in the prior art and advantages of the present invention. Other features, advantages, and embodiments of the invention will be apparent to those skilled in the art from the following description, accompanying drawings and appended claims.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic illustration of a horizontal section of the eye.

Figure 2 is a schematic illustration of the anterior portion of the eye showing the various layers of the cornea.

Figure 3 is a front view of the pocketing tool constructed according to the principles of the present invention.

Figure 4 is a detailed view of the tip section of the pocketing tool of Figure 1.

Figure 5 is a side view of the tip section of Figure 4.

Figure 6 is a perspective view of a pocketing tool having an offset handle.

Figures 7 and 8 illustrate circumferential and radial incisions respectively.

Figure 9 illustrates the use of a pocketing tool according to the principles of the present invention.

#### DESCRIPTION OF THE INVENTION

Prior to explaining the details of the inventive devices, a short explanation of the physiology of the eye is needed to appreciate the functional relationship of these intracorneal inserts or segments to the eye.

5

Figure 1 shows a horizontal cross-section of the eye with the globe (11) of the eye resembling a sphere with an anterior bulged spherical portion representing the comea (12).

10

The globe (11) of the eye consists of three concentric coverings enclosing the various transparent media through which the light must pass before reaching the light-sensitive retina (18). The outermost covering is a fibrous protective portion the posterior five-sixths of which is white and opaque and called the sclera (13), and sometimes referred to as the white of the eye where visible to the front. The anterior one-sixth of this outer layer is the transparent cornea (12).

15 .

20

25

A middle covering is mainly vascular and nutritive in function and is made up of the choroid, ciliary body (16), and iris (17). The choroid generally functions to maintain the retina (18). The ciliary body (16) is involved in suspending the lens (21) and accommodation of the lens. The iris (17) is the most anterior portion of the middle covering of the eye and is arranged in a frontal plane. It is a thin circular disc similar in function to the diaphragm of a camera, and is perforate near its center by a circular aperture called the pupil (19). The size of the pupil varies to regulate the amount of light which reaches the retina (18). It contracts also to accommodation, which serves to sharpen the focus by diminishing spherical aberration. The iris divides the space between the cornea (12) and the lens (21) into an anterior chamber (22) and the posterior chamber (23). The innermost portion of covering is the retina (18), consisting of nerve elements which form the true receptive portion for visual impressions.

The retina (18) is a part of the brain arising as an outgrowth from the fore-brain, with the optic nerve (24) serving as a fiber tract connecting the retina part of the brain with the fore-brain. A layer of rods and cones, lying just beneath a pigmented epithelium on the anterior wall of the retina serve as visual cells or photoreceptors which transform physical energy (light) into nerve impulses.

The vitreous body (26) is a transparent gelatinous mass which fills the posterior four-fifths of the globe (11). At its sides it supports the ciliary body (16) and the retina (18). A frontal saucer-shaped depression houses the lens.

The lens (21) of the eye is a transparent bi-convex body of crystalline appearance placed between the iris (17) and vitreous body (26). Its axial diameter varies markedly with accommodation. A ciliary zonule (27), consisting of transparent fibers passing between the ciliary body (16) and lens (21) serves to hold the lens (21) in position and enables the ciliary muscle to act on it.

Referring again to the cornea (12), this outermost fibrous transparent coating resembles a watch glass. Its curvature is somewhat greater than the rest of the globe and is ideally spherical in nature. However, often it is more curved in one meridian than another giving rise to astigmatism. A central third of the cornea is called the optical zone with a slight flattening taking place outwardly thereof as the cornea thickens towards its periphery. Most of the refraction of the eye takes place through the cornea.

Figure 2 is a more detailed drawing of the anterior portion of the globe showing the various layers of the cornea (12) making up the epithelium (31). Epithelial cells on the surface thereof function to maintain transparency of the cornea (12). These epithelial cells are rich in glycogen, enzymes and acetylcholine and their activity regulates the corneal corpuscles and controls the transport of water and electrolytes through the lamellae of the stroma (32) of the cornea (12).

An anterior limiting lamella (33), referred to as Bowman's membrane or layer, is positioned between the epithelium (31) and the stroma (32) of the cornea. The corneal stroma (32) are made up of lamellae having bands of fibrils parallel to each other and crossing the whole of the cornea. While most of the fibrous bands are parallel to the surface, some are oblique, especially anteriorly. A posterior limiting lamella (34) is referred to as Descemet's membrane. It is a strong membrane sharply defined from the stroma (32) and resistant to pathological processes of the cornea. The endothelium (36) is the most posterior layer of the cornea and consists of a single layer of cells. The limbus (37) is the transition zone between the conjunctiva (38) and sclera on the one hand and the cornea (12) on the other.

25

5

10

15

With that background in place, our invention centers on a pocketing tool constructed to form an intrastromal separation at a desired depth below the surface of the comea. The pocketing tool has a dissecting or delaminating tip and preferably includes an insertion stop feature positioned at a predetermined distance from the tip. As the tip of the pocketing tool is inserted vertically into the incision, the stop feature contacts the outer surface of the comea and effectively inhibits further advancement of the pocketing tool tip. With the depth of the delaminating tip controlled by the stop feature, the pocketing tool may then be manipulated to accurately create the desired separation.

5

10

15

20

25

30

The stop feature may also provide a steady reference against the surface of the cornea from which the pocketing tool may be rotated. Rotating the pocketing tool about such a reference provides an enhanced measure of control at the delaminating tip as it separates the lamella to form an initial separation or pocket. The pocketing tool is typically provided with an elongated handle positioned relative to the tip to provide the surgeon with optimum visual access and a steady grip and control as the instrument is manipulated.

Figure 3 illustrates a pocketing tool constructed according to the principles of the present invention. The pocketing tool (100) has an instrument handle (120) and a thin instrument shaft (140) terminating distally in tip section (150). Instrument handle (120) is typically knurled or coated for purposes of gripping, and may have a flat region (110) to allow the instrument to be marked with any desired identifying data.

The shaft (140) connects to the handle (120) at connecting hub (130). Connecting hub (130) securely attaches the proximal end of the shaft (140) to the handle (120). The entire corneal pocketing tool may be of a single piece of material and ground to the final net shape. Alternatively, the shaft (140) may be a separate piece and attached by way of an interference fit with mating features in the hub, or by bonding or welding or the like. The connecting hub (130) may optionally be in the form of a collet or other clamping mechanism that allows substitution of different tip instruments, such as, for example, right and left handle offset handle pocketing tools as described in detail below.

The tip section (150) can be seen more clearly in the magnified front and side views illustrated in Figures 4 and 5 respectively. Tip section (150) is constructed to have a reference region (220), which is constructed to contact the surface of the comea during

5

10

15

20

25

30 -

use, and is connected proximally to the shaft (140) and distally to a dissector (270). The reference region (220) may be a generally flat reference surface, may be curved to match the contour of the cornea, or may have any other features or construction which allows the pocketing tool to reference against the surface of the cornea. If the tip section is constructed of wire material, the reference region may be the outside surface of the wire itself.

The shaft (140) is shown disposed at an angle (230) to the plane of the reference region (220). In practice, the angle (230) is constructed to provide the surgeon with the optimum manual control and visibility for the particular surgery which is to be performed. The angle (230) is typically between about 10° to 170°, preferably between about 30° to about 90°, most preferably about 60°. A small radius (272) may be provided at the transition between the reference region (220) and the dissector (270). Radius (272) may be from about 0.01 to about 0.05 inches.

The dissector may have a variety of constructions including a relatively thin wire construction or may have a flat profile construction as shown. In Figures 4 and 5, the dissector (270) has an inner surface (274) and an outer surface (273), and is also disposed in angular relation to the reference region (220). The dissector angle (205), shown as the angle between the inner surface (274) and reference region (220), is typically less than 150°, preferably less than 110°, but may be between about 30° and about 150°, more preferably between about 60° to about 100°, most preferably about 75° as shown.

This angle between the reference region and the body of the dissector may be determined in a number of ways. When the surfaces are flat, the determination of the relative angular position is quite clear as shown in the figures. When the reference region is a curved surface or one or more dimples or protuberances the angular relationship may be defined, for example, by determining the angle between two planes that best approximate the reference region and the dissector surfaces.

Inner surface (274) and outer surface (273) generally converge at dissector tip (280). The profile of these converging dissector surfaces are created by grinding, chemical etching, machining, or the like. The dissector tip (280) may be ground sharp, or may be left with a slight radius or even a blunt tip if desired. As will be described in more detail below, the pocketing tool of the present invention allows the use of a sharper dissector tip

with less risk. The grind angle (210) between the inner surface (274) and the outer surface (273) must provide for enough material in the dissector region to impart the necessary structural rigidity as well as remaining sufficiently thin for insertion into a corneal incision. The grind angle (210) is typically between about 10° to about 50°, more preferably about 25° to about 35°, most preferably about 30°. In the side view illustrated in Figure 5, the dissector (270) may have be formed with a full radius (310) as shown. A small perpendicular hook or protrusion in the direction that is to be separated may optionally be provided at the dissector tip.

5

10

15

20

25

30

To achieve the desired size, structural integrity, and biocompatibility required for proper operation in corneal surgery, the pocketing tool (100) is typically made from stainless steel or titanium, preferably anodized titanium. For the purposes of example only, the material thickness in the vicinity of the shaft (140) and reference region (220) is typically about 0.014 to 0.020 inches. The side view width (282) of the tip section (150) is typically constructed to be somewhat smaller than the width of the incision that will be used, typically less than about one-half of the width of the expected incision. For typical incisions in the range of about 1mm to about 1.2mm, the width (282) is preferably about 0.02 inches. The downward distance (284) from the reference region (220) to the dissector tip (280) is preferably constructed to coincide with the desired depth of the corneal pocket to be formed. If for example, a pocket is to be created at a depth of 0.018 inches from the surface of the cornea, then the instrument will be constructed with a downward distance (284) of about 0.018 inches.

Because many corneal surgery procedures are performed while looking through a microscope, and thus instrument access can be significantly limited, it may be desirable to provide a corneal pocketing tool which has a handle offset from the working plane of the dissector. This allows manipulation of the dissector portion of the pocketing tool within the incision primarily by rotation of the handle about its longitudinal axis.

In contrast to the in-line configuration discussed above with reference to Figures 3-5, Figure 6 illustrates a corneal pocketing tool (400) having a handle (420) which is offset from the dissector (470), dissector tip (480), and reference region (485). In addition to the dissector (470) being offset from the longitudinal axis (405) of the handle (420), the dissector (470), dissector tip (480) and reference region (485) have been rotated

approximately 90° about a vertical axis (403) from their orientation as illustrated with regards to the in-line configuration discussed above. The handle (420) is preferably knurled to provide optimum gripping and may include one or more flat or recessed sections (410)

5

The dissector (470), dissector tip (480) and reference region (485) are constructed in the same manner as described above. Reference region (485) may connect directly to the shaft (440) or may connect by way of a straight or curved support member, such as straight support (490). Support (490) has an inclination angle (455) relative to the reference region (485) and connects to shaft (440) at connecting angle (450).

10

The pocketing tool is typically constructed such that the support (490), inclination angle (455) and connecting angle (450) result in the dissector (480) being in the desired dissector angle (460) to the reference region (485). As noted above, the dissector angle (460) may be between about 30° and 150°, more preferably between about 60° to 100°, most preferably about 75°. The access angle (453) of the handle (420) relative to the vertical axis (403) may be any angle suitable to allow the surgeon to see and manipulate the corneal pocketing tool into the incision and to begin intrastromal separation.

Preferably, access angle (453) is less than about 90°, more preferably about 70° to about 90°.

15

Depending on the position of the incision in the cornea, the direction in which pocketing is to occur, whether it is the patient's left or right eye, and the positioning of other surgical instruments, it may be desirous to have an opposite-handed offset to that shown in Figure 6. The principles described above apply equally well to a pocketing tool

having an oppositely-handed offset.

desired to create an intrastromal pocket.

20

To form a pocket or separation between the stromal layers of the comea, the pocketing tool is inserted into a partial depth incision (610) as shown in Figure 9. The partial depth incision (610) may be of any type or orientation from which intrastromal pocketing is to begin. The incision may be a circumferential type incision (510) for forming a radial pocket in the comea 500 as illustrated in Figure 7 or may be a radial type incision (550) for circumferential pocketing, for example, to form an intrastromal channel (560) as illustrated in Figure 8. Preferably, the incision is made to the depth at which it is

25

The dissector (270) of the corneal pocketing tool is advanced into the incision (610) until reference region (220) comes into contact with the surface (605) of the cornea (620). The relatively large contact area of the reference region (220) ensures that there will be no significant damage to the corneal tissue as the surgeon applies the downward pressure necessary for insertion of the dissector (270) into the incision (610). The downward pressure applied to the corneal pocketing tool by the surgeon is absorbed by the reference region (220) rather than by the dissector tip (280) against the bottom of the incision. For this reason, the dissecting tip may be relatively sharp to facilitate pocketing, without risk to the surrounding tissue.

10

15

5 .

Because the distance from the reference region (220) to the dissector tip (280) corresponds to the desired depth for corneal pocketing (and coincidentally with the bottom of the partial depth incision), once the surgeon appreciates the tactile indication that the reference region (220) is in contact with the corneal surface (605) it is known that the dissector tip (280) is at the proper depth below the corneal surface (605). Thus, the surgeon is not required to use the dissecting tip to feel for the bottom of the incision, but instead proper depth of the dissecting tip is indicated by the resistance to further advancement of the reference region (220) against the corneal surface (605). This provides the surgeon with greatly improved tactile feedback that the instrument is fully inserted and reduces the risks of tissue damage or separating the tissue at an incorrect depth.

20

With the dissector 270 in place within the incision (610) as shown in Figure 9, an intrastromal separation or pocket is initiated simply by pivoting or rotating the instrument in the direction indicated by the arrow (640). This allows the dissector (270) and dissecting tip (280) to rotate about the radius (272), forcing the stromal layers to delaminate by operation of the dissecting tip (280) at the proper depth below the corneal surface (605). The amount of rotation required is typically in the range of 10° to 90°, preferably around 45°.

30

25

As the instrument is rotated, the depth of the dissecting tip remains controlled in part by the reference region (220) as it rotates about radius (272), and a separation or pocket (630) is created. This rotational movement about the transition between the reference region (220) and the dissector (270) results at first in motion predominantly parallel to the corneal surface (605) and then begins to lift the separated tissue as rotation

is furthered. If the width of the incision (610) is greater than the width of the dissector (270), it may be desirable to maneuver the dissector across the width of the incision either while holding the dissector (270) in the rotated position or by releasing and repositioning the dissector (270) to a new position along the width of the incision (610).

5

The rotation of the dissector (270) about radius (272) is ultimately accomplished by manipulation of the handle of the corneal pocketing tool. When the corneal pocketing tool has an in-line configuration, as illustrated in Figure 3, the handle is maneuvered in the direction indicated by the arrow (107). For the offset corneal pocketing tool (400) illustrated in Figure 6, the instrument requires rotational manipulation about the longitudinal axis similar to that indicated by the arrow (407). In this case, the space requirements to facilitate the overall displacement of the handle is considerably less than that of the in-line configuration.

10

Once the desired separation or pocket has been started using the present invention, various other instruments may then be inserted through the incision to enlarge or otherwise modify the pocket. For example, a larger pocket or channel may be created using a stromal spreader or various arcuate channeling tools inserted through the incision and into the initial pocket formed by the corneal pocketing tool described above.

15

All references cited above are hereby incorporated herein by reference.

20

The above is a detailed description of a particular embodiment of the invention. It is recognized that departures from the disclosed embodiment may be made within the scope of the invention and that obvious modifications will occur to a person skilled in the art. The full scope of the invention is set out in the claims that follow and their equivalents. Accordingly, the claims and specification should not be construed to unduly narrow the full scope of protection to which the invention is entitled.

#### WE CLAIM AS OUR INVENTION:

5

10.

15

20

25

1. A surgical instrument for separating the lamella of a cornea, comprising a reference region adapted to contact the surface of said cornea and a dissector, said dissector and said reference region being oriented at an angle of less than about 110 degrees to said reference region.

- 2. The surgical instrument of claim 1 wherein said angle is between about 60 degrees to about 100 degrees.
- 3. The surgical instrument of claim 1 wherein said angle is less than about 90 degrees.
  - 4. The surgical instrument of claim 3 wherein said angle is about 75 degrees.
- 5. The surgical instrument of claim 1 wherein said reference region comprises a substantially planar surface.
- 6. The surgical instrument of claim 1 wherein said reference region comprises a curved surface having a radius of curvature between about 6 mm to about 10 mm.
- 7. The surgical instrument of claim 1, wherein said reference region and said dissector converge at a radius.
- 8. The surgical instrument of claim 1, further comprising an elongate handle connected to said reference region.
- 9. A surgical instrument for separating the lamella of a comea at the base of a partial-depth incision, comprising a reference surface and a dissector positioned at an angle relative to said reference surface such that the free advancement of said dissector into said incision is prevented by contact of said reference surface against said comea.
- 10. A surgical instrument for separating the lamella of a comea at the base of a partial-depth incision, comprising a tip section and a handle; said tip section having a

dissector adapted to enter the incision and a reference region adapted to rest against the surface of the cornea.

- 11. The surgical instrument of claim 10, wherein said dissector and said reference region have a common intersection and whereby rotation of said handle causes said tip section to pivot about a point near said intersection.
- 12. The surgical instrument of claim 10 wherein said dissector is at an angle of less than about 110° to said reference region.
- 13. The surgical instrument of claim 11, wherein said intersection is a radiused surface connecting said reference region to said dissector.
- 14. A method of creating an intralamellar pocket at the base of a partial-depth corneal incision comprising the steps of
- (a) inserting a dissector of an instrument having a reference surface in angular relation to said dissector into said incision until the reference surface contacts the surface of the cornea; and
- (b) rotating the instrument about the vertex of the intersection of the reference surface and the dissector, whereby the distal dissecting tip is caused to separate the lamella of the cornea.

5

10





FIG. 2

SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)







FIG. 5

FIG. 4







# INTERNATIONAL SEARCH REPORT

Int itional Application No PCT/US 98/26966

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 A61F9/013

According to International Patent Classification (IPC) or to both national classification and IPC

#### B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols) IPC 6 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT					
Calegory *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.			
X,P	WO 98 46192 A (GANDIONCO ISIDRO MATIAS; SCHOLL JOHN ANTHONY (US); KERAVISION INC) 22 October 1998 see figure 12 see page 17, line 9 - line 21 see page 19, paragraph 1 see claim 38	1-5,7-13			
X A	US 5 405 355 A (UPDEGRAFF STEPHEN A ET AL) 11 April 1995 see figure 1 see column 2, line 61 - column 3, line 13	1,2,5, 8-10,12 3,11			
X ,	US 5 222 967 A (RAE CAROL A ET AL) 29 June 1993 see column 4, line 25 - line 40 see claims 1,2 see figure 6	1,2,5,9, 10,12 3,11			

Further documents are listed in the continuation of box C.	Patent family members are listed in annex.
*Special categories of cited documents:  "A" document defining the general state of the art which is not considered to be of particular relevance  "E" earlier document but published on or after the international filling date  "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  "O" document referring to an oral disclosure, use, exhibition or other means  "P" document published prior to the international filling date but later than the priority date claimed	<ul> <li>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</li> <li>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</li> <li>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</li> <li>"&amp;" document member of the same patent family</li> </ul>
Date of the actual completion of the international search	Date of mailing of the international search report
8 April 1999	15/04/1999
Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl. Fax: (+31-70) 340-3016	Mary, C

## INTERNATIONAL SEARCH REPORT

Inti Ional Application No PCT/US 98/26966

Category •	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No.	
A	US 5 411 510 A (FUGO RICHARD J) 2 May 1995 see figure 2 see column 3, line 48 - column 4, line 26	1-3,5, 8-12	
A	WO 97 04726 A (KRITZINGER MICHIEL S; UPDEGRAFF STEPHEN A (US)) 13 February 1997 see figure 1 see claims 1,4	1,6	
ŀ			
•			
.			
		•	
,			
		•	
.			
		. '	
		•	
		•	
1	,	•	

...ternational application No.

## INTERNATIONAL SEARCH REPORT

PCT/US 98/26966

Box i Observations where certain claims wire found unsearchable (Continuation of item 1 of first sheet)
This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:
1. X Claims Nos.: 14 because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. Claims Nos.: because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).
Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)
This international Searching Authority found multiple inventions in this international application, as follows:
As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
this learnest Search Benoti
3. As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
The additional search fees were accompanied by the applicant's protest.
Remark on Protest  No protest accompanied the payment of additional search fees.

Form PCT/ISA/210 (continuation of first sheet (1)) (July 1998)

## INTERNATIONAL SEARCH REPORT

Information on patent family members

Int tional Application No PCT/US 98/26966

Patent document cited in search report		nt .	Publication date	Patent family member(s)		Publication date	
WO	9846192	Α	22-10-1998	AU -	7116998 A	11-11-1998	
US	5405355	Α	11-04-1995	. NONE			
US	5222967	Α	29-06-1993	AU	3923993 A	18-11-1993	
			-	· CA	2110796 A	28-10-1993	
			•	EP	0593705 A	27-04-1994	
				JP	7505324 T	15-06-1995	
				US	5423840 A	13-06-1995	
				WO	9320761 A	28-10-1993	
US	5411510	Α	02-05-1995	NONE			
WO	9704726	. A	13-02-1997	US	5779711 A	14-07-1998	
				AU	6602596 A	26-02-1997	
			*	ΑU	6602696 A	26-02-1997	
				· AU	.6639096 A	26-02-1997	
	•		. •	WO	9704725 A	13-02-1997	
			·	- WO	9704727 A	13-02-1997	

#### WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: A61F 9/013

(11) International Publication Number:

WO 99/30656

A1

(43) International Publication Date:

24 June 1999 (24.06.99)

(21) International Application Number:

PCT/US98/26966

(22) International Filing Date:

16 December 1998 (16.12.98)

(30) Priority Data:

08/993,445

18 December 1997 (18.12.97)

(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application

US

08/993,445 (CIP)

Filed on

18 December 1997 (18.12.97)

(71) Applicant (for all designated States except US): KERAVI-SION, INC. [US/US]; 48630 Milmont Drive, Fremont, CA 94538-7353 (US).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): GANDIANCO, Isidro [US/US]; 36520 Alder Court, Fremont, CA 94536 (US). SCHOLL, John, A. [US/US]; 14 Woodranch Circle, Danville, CA 94506 (US).
- (74) Agents: BECKING, Frank, P. et al., Morrison & Foerster LLP, 755 Page Mill Road, Palo Alto, CA 94304-1018 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published

With international search report. With amended claims.


Date of publication of the amended claims:

10 September 1999 (10.09.99)

(54) Title: CORNEAL POCKETING TOOL

#### (57) Abstract

The invention relates to a comeal pocketing tool for separating the lamella of the comea. The comeal pocketing tool has a dissector portion for insertion into a corneal incision and a reference surface or region adapted to contact the comea. As the dissector is advanced into the corneal incision the reference region comes into contact with the surface of the comea and resists further advancement of the dissector. As the reference region is moved in a clockwise or counterclockwise direction, the dissector portion follows in the same direction forming a pocket in the comea.



## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia .
AM	Armenia .	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia ·	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad .
, BA	- Bosnia and Herzegovina	GE	Georgia	MD .	Republic of Moldova	TG	Togo
BB	Barbados	GH	. Ghana	MG	Madagascar	TJ	Tajikistan .
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	. GR	Greece	•	Republic of Macedonia	TR	Turkey .
BG	Bulgaria	HU	Hungary	ML	Mali	.TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	· UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ.	Uzbekistan .
CF.	Central African Republic	JP	Јарал	NE	Niger	VN	Viet Nam .
CG	Congo	KE	Kenya .	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	· zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon	•	Republic of Korea	PL	Poland		
CN	China ·	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

#### AMENDED CLAIMS

[received by the International Bureau on 15 June 1999 (15.06.99); original claims 1, 9 and 10 amended; new claims 15-21 added; remaining claims unchanged (3 pages)]

- 1. A surgical instrument for separating the lamella of a comea, comprising a reference region adapted to contact the surface of said comea and a dissector having a tip with an end forming a leading edge, said dissector and said reference region being oriented at an angle of less than about 110 degrees to each other.
- 2. The surgical instrument of claim 1 wherein said angle is between about 60 degrees to about 100 degrees.
- 3. The surgical instrument of claim 1 wherein said angle is less than about 90 degrees.
  - 4. The surgical instrument of claim 3 wherein said angle is about 75 degrees.
- 5. The surgical instrument of claim 1 wherein said reference region comprises a substantially planar surface.
- 6. The surgical instrument of claim 1 wherein said reference region comprises a curved surface having a radius of curvature between about 6 mm to about 10 mm.
- 7. The surgical instrument of claim 1, wherein said reference region and said dissector converge at a radius.
- 8. The surgical instrument of claim 1, further comprising an elongate handle connected to said reference region.
- 9. A surgical instrument comprising a reference portion having a surface and a dissector portion adapted for separating the lamella of a cornea, said dissector portion extending from said reference portion and positioned at an angle relative to said reference surface such that the free advancement of said dissector into said incision is prevented by contact of said reference surface against said cornea.
- 10. A surgical instrument comprising a reference region, a tip section and a handle section said tip section having a dissector adapted to enter a partial-depth incision

5

10

15

20

in a cornea and separate the lamella of the cornea at a depth limited by said reference region which is adapted to rest against the surface of the cornea.

- 11. The surgical instrument of claim 10, wherein said dissector and said reference region have a common intersection and whereby rotation of said handle causes said tip section to pivot about a point near said intersection.
- 12. The surgical instrument of claim 10 wherein said dissector is at an angle of less than about 110° to said reference region.
- 13. The surgical instrument of claim 11, wherein said intersection is a radiused surface connecting said reference region to said dissector.
- 14. A method of creating an intralamellar pocket at the base of a partial-depth corneal incision comprising the steps of
- (a) inserting a dissector of an instrument having a reference surface in angular relation to said dissector into said incision until the reference surface contacts the surface of the cornea; and
- (b) rotating the instrument about the vertex of the intersection of the reference surface and the dissector, whereby the distal dissecting tip is caused to separate the lamella of the cornea.
- 15. The instrument of claim 1 wherein said leading edge has a shape selected from rounded shapes and flattened shapes.
- 16. The instrument of claim 1 wherein said tip has a profile at least substantially perpendicular to said leading edge, said profile defining an angle between about 10° to about 50°.
- 17. The instrument of claim 16 wherein said profile defines an angle between about 25° and about 35°.

20

. 5

10

5

- 18. The instrument of claim 1 wherein said dissector tip is blunt.
- 19. The instrument of claim 9 wherein said dissector has an end with a leading edge having a shape selected from rounded shapes and flattened shapes.
- 20. The instrument of claim 19 wherein said end has a profile at least substantially perpendicular to said leading edge, wherein said profile defines an angle between about 10° to about 50°.
- 21. The instrument of claim 20 wherein said profile defines an angle between about 25° and about 35°.

# THIS PAGE BLANK (USPTO)